

Mechanical Track Jacks

▼ Shown: 02025 (A8), 02000 (A5) and 02075 (A17)



- Three lightweight, easy to carry models fit all track applications
- Solid cast base and large grooved toe for stable jacking
- Heat-treated, forged components for extra strength and longer life
- Rust-proof tension spring maintains full pawl engagement

A Series

Rated Capacity per Jack:

15 tons

Stroke:

5.25-13 inch



Square Drive Sockets

All models feature square drive sockets for use with 1½ inch square by 5-foot-5 inch standard railroad lining bars.



Quick-trip Mechanism

The Quick-trip mechanism allows the track jack to be instantly tripped while under load. Lower the load effortlessly by engaging the lifting pawl in the retaining pawl and complete one down-stroke with the lining bar. Track jacks are designed for use with standard lining bars.

▼ Mechanical Track Jacks provide fast and dependable lifting.



Capacity (ton)	Stroke (in)	Model No.	Description	Minimum Height		Base Area (in)	Max. Handle Effort/Ton (lbs)	Weight (lbs)
				Toe (in)	Cap (in)			
15	5.25	02000	Mechanical Track Jack, A5	2.00	11.00	2.50 x 3.75	33	30
15	7.75	02025	Mechanical Track Jack, A8	2.00	15.62	2.50 x 3.75	33	37
15	13.00	02075	Mechanical Track Jack, A17	2.00	22.62	2.50 x 3.75	33	50